



M6X63L-FH - LOK
BOLT @ 457mm O.C.

4MM THK.-EXTRUDED
ALUMINUM
CENTER PLATE
(HEAVY DUTY)

CONTINUOUS
ALUMINUM
SIDEFRAME

FLOOR FINISH
(BY OTHERS)

28

NON SHRINK GROUT
(BY OTHERS)

M6X50L- CONCRETE
SLEEVE ANCHOR
@ 457mm O.C. (TYP.)

25

NOTE:
ALL DIM. ARE IN MM



ONTARIO SPECIALTY ARCHITECTURE
PO Box 392567, Office No. 1404,
Metropolis Tower, Business Bay, Dubai, U.A.E.
Tel: +9714 2776760, Fax: +9714 2776736
sales@ontariosa.com
Web Site: www.ontariosa.com

MIN. JOINT OPENING	NOMINAL JOINT OPENING	MAX. JOINT OPENING	EXPOSED SURFACE	OVERALL WIDTH	OVERALL HEIGHT
0.75"(19mm)	1.00"(25mm)	1.25"(32mm)	2.87"(73mm)	3.62"(92mm)	1.09"(28mm)

DESIGN RIGHTS
This drawing and designs contained hereon are proprietary and confidential property of OSA. These should not be used for any purpose other than what it is issued for. This drawing should not be copied, modified, distributed or used without permission from OSA. Copyright and Intellectual Property rights are applicable.

DISCLAIMER
OSA reserves the right to discontinue the design or modify the existing design without prior notice.

MODEL NO:
FWTBF1HD

PROJECT:
CLIENT:
DRAWING NO.:

DATE:

APPLICATION:
Floor to Wall